



# Product Safety Data Sheet

**Product:** 4112 / 4127  
4112EPS / 4127EPS

**PSDS No.:** 1002  
**ISSUE DATE:** 9/13/07  
**REV. DATE:**

## Section I - Product Identification

**Manufacturer's Name**  
Xerox Corporation

**Emergency No. EH&S Inquires**  
(585) 422-2177 (800) 828-6571

**Manufacturer's Address**  
800 Salt Road  
Webster New York 14580

**Product Designation**  
Copier / Printer, Printer only

**Product Identifier:**  
EPB-3

## Section II - Electrical Information

<b>Line Voltage</b> (Volts) 208-240	<b>Line Current</b> (Amps) 12	<b>Freq.</b> (Hertz) 50/60	<b>Branch Cir. Protection</b> (Amps) 15
---	-------------------------------------	----------------------------------	---

### Line Cord/Plug Specification

Power Cord is supplied

### Power Consumption(Watt hrs.)

Running:	2,194
Standby:	375
Low Power:	120
Sleep mode:	13
Plug in off mode:	0

### Agency Approvals

CAN / CSA  
Energy Star TEC

## Section III - Supplies

### Material Safety Data Sheet

Black Toner	A-1016
Developer Black	B-2006
Drum Cartridge	C-3009

## Section IV - Environmental Information

**Product Size\*\*\***  
(Centimeters / Inches)  
D: 1455 / 57  
W: 2545 / 100  
H: 781 / 30

**Heat Emission\***  
(BTU/HR)  
Running: 7492  
Standby: 1280

**Environmental Limitations**  
Min Max  
Relative Humidity 15-85 (%)  
Ambient Temp (Tma). 32 (°C)

**Weight\*\*\***  
(K Grams / Lbs.)  
( 553 / 1219 )



**Product: 4112 / 4127  
4112EPS / 4127EPS**

**PSDS No.: 1002**

**Section V - Emission/Exposure Information\*\***

**Light Source:**

Class 1 Laser Product containing an embedded Class 3B laser

**Accession Number**

0421968-00

**Electromagnetic Emissions**

US / Canada FCC Part 15 Class A

**AUDIBLE NOISE**

System Configuration: IIT+DADF+UI+IOT+HCF+Finisher+MSI

**Operating Conditions**

**Sound Power Level B(A)**

Standby	5.78
Continuous	7.90
Impulse	8.29

**Ozone**

Daily Copy Volume: 15000      Copies/ hours: 2 hours  
Room Size: 50 m<sup>3</sup>

Concentration Based on Simulation Model: 0.005 mg/m<sup>3</sup>

**Dust**

0.024 mg/m<sup>3</sup>

**Styrene**

0.015 mg/ m<sup>3</sup>

**Section VI - Product Recycling and Disposal**

Xerox operates a worldwide equipment takeback and reuse/recycle program. Contact your Xerox sales representative (1-800-ASK-XEROX) to determine whether this Xerox product is part of the program. For more information about Xerox environmental programs, visit [www.xerox.com/environment](http://www.xerox.com/environment).

If you are managing the disposal of your Xerox product, please note that the product contains lead and other materials whose disposal may be regulated due to environmental considerations. The presence of lead is fully consistent with global regulations applicable at the time that the product was placed on the market. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: [www.eiae.org](http://www.eiae.org)."

\* Based on a five minute average

\*\* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.

\*\*\* Machine configuration, Full System = IIT+DADF+UI+IOT+HCF+Finisher+MSI